

SRK/SRC		20ZSX-W (B)(T)	25ZSX-W (B)(T)	35ZSX-W (B)(T)	50ZSX-W (B)(T)	60ZSX-W (B)(T)
Prestaties koelen						
Capaciteit	<i>kW</i>	2,0(0,9~3,4)	2,5(0,9~3,87)	3,5(0,9~4,5)	5,0(1,0~6,2)	6,1(1,0~6,9)
Jaarlijks energieverbruik	<i>kW/h</i>	70	85	129	211	274
S.E.E.R.		10,0	10,3	9,5	8,3	7,8
Energielabel		A+++	A+++	A+++	A++	A++
Werkbereik	$^{\circ}\text{C}$	-15 tot +46	-15 tot +46	-15 tot +46	-15 tot +46	-15 tot +46
Prestaties verwarmen						
Capaciteit	<i>kW</i>	2,7(0,8~5,5)	3,2(0,8~6,0)	4,3(0,8~6,8)	6,0(0,6~8,2)	6,8(0,6~8,8)
Capaciteit (-10 $^{\circ}\text{C}$)	<i>kW</i>	2,8	3,0	3,4	4,5	5,2
Jaarlijks energieverbruik	<i>kW/h</i>	754	808	934	1341	1551
S.C.O.P.		5,2	5,2	5,1	4,7	4,7
Energielabel		A+++	A+++	A+++	A++	A++
Werkbereik	$^{\circ}\text{C}$	-20 tot +24	-20 tot +24	-20 tot +24	-20 tot +24	-20 tot +24
Gegevens binnendeel		SRK20ZSX-W (B)(T)	SRK25ZSX-W (B)(T)	SRK35ZSX-W (B)(T)	SRK50ZSX-W (B)(T)	SRK60ZSX-W (B)(T)
Luchtvolume laag/hoog	<i>m³/h</i>	360/678	402/732	438/786	468/858	534/978
Geluidsvermogen max.	<i>dB(A)</i>	53	55	58	59	62
Geluidsdruk laag/hoog	<i>dB(A)</i>	19/38	19/39	19/43	22/44	22/48
Afmetingen (HxBxD)	<i>mm</i>	305x920x220	305x920x220	305x920x220	305x920x220	305x920x220
Gewicht	<i>kg</i>	13,0	13,0	13,0	13,0	13,0
Condensaansluiting	<i>mm</i>	16	16	16	16	16
Gegevens buitendeel		SRC20ZSX-W	SRC25ZSX-W	SRC35ZSX-W	SRC50ZSX-W	SRC60ZSX-W
Luchtvolume	<i>m³/h</i>	1860	1860	2160	2340	2490
Geluidsvermogen max.	<i>dB(A)</i>	56	57	61	63	65
Geluidsdruk silent mode	<i>dB A</i>	33	35	38	42	42
Afmetingen (HxBxD)	<i>mm</i>	640x871x290	640x871x290	640x871x290	640x871x290	640x871x290
Gewicht	<i>kg</i>	43,5	43,5	43,5	45,0	45,0
Voeding	<i>v/pH/Hz</i>	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50